

**TVT**

*Secure The World With You*

**HD**CCTV  
Over Coax



**1080P** DISPLAY

**720P** RECORD

**720P** PLAYBACK



**TD-2708AS-S**

**AHD DVR**



HD



H.264



DDNS



Network



PTZ



Audio



MIC



Mobile



CMS



USB



Mouse



E-mail


## Introduction

TD-2708AS-S series are standard 8 CH real time 720P high definition hybrid DVRs with ability to connect analog and IP cameras simultaneously, which adopt the standard H.264 high profile compression format and the most advanced SOC technique to ensure real time recording in each channel and realize outstanding robustness of the system. TD-2708AS-S support 8 CH video input, 1 CH audio input, simultaneous 8 CH real time playback. The series of product can meet different security requirements of home, financial, commerce, enterprise, transportation and government, etc.

## Characteristics

- 8 CH AHD video input, 720P / WD1 / D1 real time recording
- Support 1 CH IPC 720P recording
- Adopt standard H.264 high profile compression format to get high-quality video at much lower bit rate
- Intuitive and user-friendly Graphics User Interface ( GUI ), window style operation by mouse
- Multi-mode recording: manual / timer / motion
- Playback : 8 CH simultaneously playback
- Search: time / calendar, events ( motion )
- Express and flexible backup via USB, network
- Pentaplex: preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol, IE browse and CMS supported
- Remote control via IE or CMS : preview, playback, backup, PTZ and configuration
- Dual stream technology to encode recording stream and network stream respectively. User can adjust network stream to fit bandwidth without changing recording quality
- Multi-user online simultaneously
- Authorization management, log review and device status review
- HDMI 1080P output, true high resolution display
- Support PTZ preset and auto cruise, up to 128 presets and 8 cruises
- Powerful smart phone surveillance supporting iPhone, Android
- Support NAT function, support QR code scanning by mobile phone
- Complete SDK software available, easy to integrate with other applications

## Dimensions



## Specification

Model		TD-2708AS-S
System	Compression	Standard H.264 High Profile
	CPU	Cortex A9
	OS	Embedded Linux
Video	Input	BNC x 8 Support 720P@25 / 30fps, 960H, D1 input
	IP Input / Access Bandwidth	IPC x 1 / 6Mbps
	Output	HDMI x 1 : 1920 x 1080 / VGA x 1 : 1920 x 1080
Audio	Input	RCA x 1
	Output	RCA x 1
	2-way audio	Take up channel one audio input
Record	Resolution	720P : 1280 x 720, WD1, D1
	Frame Rate	200 fps (PAL) 240 fps (NTSC)
	Bit rate	1M ~ 4Mbps
	Encode	VBR / CBR
	Quality	6 Level
	Mode	Manual, timer, motion
	File manager	Lock, unlock, reserving time
IP Input	Resolution	720P
	Frame Rate	25 fps (PAL) / 30 fps (NTSC)
Play back	Playback	8 CH
	Search	Time / calendar search, event ( motion)
	Smart Search	Highlighted date and time to display the channel record
	Function	Play, Pause, FF, FB, Digital zoom
Alarm	Mode	Motion, video loss
	Input	No
	Output	No
	Triggering	Record, PTZ move, e-mail, etc
Network	Interface	RJ45 10M/100M adaptive ethernet network port x 1
	Protocol	TCP / IP, UDP, DHCP, DNS, PPPOE, DDNS
	Others	10 users online, dual stream
Cell phone	OS	iPhone, Android
	Function	Multi-screen surveillance ( for certain model), record, snapshot, PTZ control, save the device list
I/O	HDD	SATA x 1
	RS485	RS485 x 1, connect to PTZ or keyboard
	USB	USB 2.0 x 2, one for mouse, another for USB backup device
	IR controller	Optional
Others	Power supply	DC 12V
	Consumption	< 8W ( without HDD )
	Dimensions	255 mm * 210 mm * 42 mm ( W * D * H )
	Work Environment	- 10 °C ~ 50 °C , 10 % ~ 90 % Humidity

